



PASSENGER DRINK HOLDER WITH STAINLESS CUP 1485

FITS-1/2" PASSENGER GRAB RAILS ON ELECTRA/TOUR GLIDES OR UNIVERSAL FIT ON 1/2", 5/8", OR 3/4" TUBES

PARTS INCLUDED

- 1 3/4" bar clamp
1 Reducing Ring Kit
1 Universal Drink Holder Assembly
1 Stainless Steel Cup
1 Hardware Kit
1 Thumb Nut
1 5/16" Split Lock Washer
2 Shim Washers
1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KURYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of hex wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE - Please note that all hardware included may not be used for installation

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

STEP 2 Determine a suitable mounting location for the Drink Holder. Ensure that the mounting location will not interfere with the normal operation of the motorcycle.

WARNING! IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer...

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
• The product must be properly installed, maintained and operated under normal conditions.
• Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
• Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
• Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
• Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today-select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



**CAUTION!** Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

**ATTENTION!** Determine the mounting location and orientation of the Drink Holder before fully tightening the two screws. The clamp may leave marks on the rail when tightened down.

**STEP 3** Remove the two screws from the clamp.

**STEP 4** Hold the clamp halves together on the rail in the desired location. Determine which (if any) aluminum spacers are needed to ensure proper fitment to the intended rail. Add anti seize to the threads and re-install the two screws from Step 3; leave the screws finger tight for now.

**STEP 5** Insert the Drink Holder pivot shaft into the pivot hole in the clamp. Apply a small amount of anti seize to the threads.

**STEP 6** As shown in PIC 1, place the 5/16" split lock washer on the stud and secure the Drink Holder to the clamp with the thumb nut.

**STEP 7** Once you have the Drink Holder in the desired position, ensure that it will not interfere with the proper operation of the motorcycle.

**STEP 8** Tighten the two screws in the clamp and the thumb nut.

**CAUTION!** The adjustability of the Drink Holder was not intended to prevent spills.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

**WARNING! TO PREVENT POSSIBLE LOSS OF CONTROL, WHICH COULD RESULT IN A POSSIBLE INJURY OR DEATH, WE DO NOT RECOMMEND REMOVING AND REPLACING CUP WHILE RIDING THE MOTORCYCLE.**

*Ride On!*

**Küryakyn**<sup>®</sup>

PIC. 1



**PAGE**

**2**