

INSTALLATION INSTRUCTIONS

REAR TURN SIGNAL BAR FOR STREET GLIDE & ROAD GLIDE, GLOSS BLACK

5407

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

1	Rear Turn Signal Light Bar	1	Description
		2	1/4 Split Lock Washer
		2	6-32 X .3 Button Head Cap Screws
		2	Shrink Tubing 2" X .125
		2	1/4-20 X .50 Button Head Cap Screws
		6	18-22 AWG Sealed Butt Connector

YOU WILL ALSO NEED:

Set of Combination Wrenches, Set of Hex Wrenches, Phillips Screwdriver, Wire Cutter/Crimper, Test Light

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool. Remove main fuse.

WARNING A FACTORY SERVICE MANUAL WILL BE HELPFUL IN PERFORMING THIS INSTALLATION. DO NOT ATTEMPT TO PERFORM THIS INSTALLATION IF YOU ARE NOT CONFIDENT IN YOUR ABILITY TO COMPLETE ALL OF THE STEPS IN THE PROCEDURE; CONSULT A TRAINED TECHNICIAN. IMPROPER INSTALLATION COULD RESULT IN SERIOUS INJURY OR DEATH.

STEP 2 Refer to PIC 1 and 2. Disconnect and remove existing rear light bar.

Note: Removal process may vary between models, refer to service manual for assistance.



INSTALLATION INSTRUCTIONS

REAR TURN SIGNAL BAR FOR STREET GLIDE & ROAD GLIDE, GLOSS BLACK 5407

5407

-CONTINUED-

STEP 3 Refer to PIC 3 and 4. Remove license plate bracket from the existing light bar.



PIC 3



PIC 4

STEP 4 Refer to PIC 5 and 6. Remove the license plate L.E.D. light from the light bar. Cut the harness wires connecting the harness to the two individual lights on the light bar.



PIC 5



PIC 6

STEP 5 Refer to PIC 7 and 8. Locate Turn Signal Light Bar and Hardware Kit.




PIC 7



PIC 8

STEP 6 Refer to PIC 9 and 10. Splice turn signal light bar wires with the newly cut harness wires, using the provided six (6) sealed butt connectors. Connect the blue to blue, the purple to purple, and the black to black.



PIC 9



PIC 10

STEP 7 Refer to PIC 11. Align and fasten the L.E.D. license plate light to the light bar, using the provided two (2) 6-32 x .3" button head cap screw.



PIC 11

STEP 8 Refer to PIC 12 and 13. Align and fasten the license plate to the new light bar, using the provided two (2) 1/4-20 x .50" button head cap screws and two (2) split lock washers.



PIC 12



PIC 13

INSTALLATION INSTRUCTIONS

REAR TURN SIGNAL BAR FOR STREET GLIDE & ROAD GLIDE, GLOSS BLACK

5407

-CONTINUED-

STEP 9 Refer to PIC 14 and 16. Feed wiring harness back through the larger hole in the rear fender. Align the light bar assembly with the two mounting holes in the rear fender. Be sure the supplied gasket on the light bar is properly in place. Locate OEM hardware removed in Step 1 and fasten light bar to rear fender. Fully tighten hardware.



STEP 10 Install the new light bar in the reverse order the old one was removed.

STEP 11 Reinstall main fuse. Check to make sure all lights work properly before riding bike.

WARNING

ENSURE PROPER LIGHT OPERATION BEFORE RIDING THE MOTORCYCLE. VISIBILITY IS A MAJOR CONCERN FOR MOTORCYCLISTS. A LIGHT MALFUNCTION COULD RESULT IN DEATH OR SERIOUS INJURY.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice