

## INSTALLATION INSTRUCTIONS

### FRONT OR REAR SPLINE PEG ADAPTERS, SILVER

8906

#### THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

**WARNING** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

**NOTICE** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

#### ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 2 Splined Peg Adapters
- 2 Spacers

#### YOU WILL ALSO NEED:



Small flat-blade screwdriver

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE SILVER PARTS WILL BE THE SAME.

**NOTICE** THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- INSTALL THE FRONT PEG ADAPTERS:**
- STEP 2** Use a small flat-blade screwdriver to remove the E-clip from the footrest pivot-pin; save it for later.
- STEP 3** Remove the pin and existing footrest; save the pin, E-clip, and return spring for later use.
- STEP 4** Refer to PIC 1. Assemble the return spring in the new Splined Adapter as shown. Insert one of the included Spacers as shown; the Spacer can be inserted on the top or bottom side allowing for approx. 1/4" of height adjustment; the Spacer will secure the spring in the Adapter.
- STEP 5** Insert the long leg of the spring in the mount hole as shown in PIC 2. Press the Adapter in to align the holes; secure with the pin and E-clip.
- STEP 6** Repeat for the other side.
- STEP 7** Finish the installation by following the procedures included with the footrests (sold separately).

**WARNING** BEFORE OPERATING THE MOTORCYCLE, ENSURE THAT THE END USER IS FAMILIAR WITH THE POSITION/FUNCTION CHANGES DUE TO THE INSTALLATION OF THIS PRODUCT. UNFAMILIAR CONTROLS CAN LEAD TO LOSS OF CONTROL CAUSING SERIOUS INJURY OR DEATH!



## INSTALLATION INSTRUCTIONS

### FRONT OR REAR SPLINE PEG ADAPTERS, SILVER


8906

-CONTINUED-

#### INSTALL THE REAR PEG ADAPTERS:

*Note: Ensure that the detent ball and spring are secured after the pivot pin is removed; the detent ball is very small and easy to lose.*

- STEP 8** Use a small flat-blade screwdriver to remove the E-clip from the footrest pivot-pin; save it for later. Carefully remove the existing footrest; save the detent ball and spring for later use.
- STEP 9** Insert the detent ball in the Adapter on the upper-side to prevent it from falling out during installation. Sandwich the spring and Adapter in between the mount on the bike as shown in PIC 3 and 4.
- STEP 10** Refer to PIC 4. Align the holes and secure with the pin and E-clip.
- STEP 11** Repeat for the other side.
- STEP 12** Finish the installation by following the procedures included with the footrests (sold separately).



#### WARNING

**BEFORE OPERATING THE MOTORCYCLE, ENSURE THAT THE END USER IS FAMILIAR WITH THE POSITION/FUNCTION CHANGES DUE TO THE INSTALLATION OF THIS PRODUCT. UNFAMILIAR CONTROLS CAN LEAD TO LOSS OF CONTROL CAUSING SERIOUS INJURY OR DEATH!**

#### NOTICE

**IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.**

#### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

#### RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice).

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts (s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice)

**KURYAKYN.COM**

866 277 9598 | [INFO@KURYAKYN.COM](mailto:INFO@KURYAKYN.COM)

454 COUNTY ROAD VV SOMERSET, WI 54025

PAGE 2

308906

DPF-MRK-003 REV A 9/11/17

